

HAVERKAMP GmbH

DIN Normen / EN Normen

Durchschusshemmung nach prEN 1063

Klasse	Waffenart	Kaliber	Geschossart	Geschoss- masse in g		Schussent- fernung in m	Geschoss- geschw. (m/sek.)	Treffer	Trefferab- stand in mm
				+/- 0,1	+/- 0,5				
BR1	Gewehr	.22 LR	RK/Blei	2,6	10	10	360	3	120
BR2	Pistole	9 mm Para	VM/RK/WK	8	5	5	400	3	120
BR3	Revolver	.357 Magnum	VM/KS/WK	10,2	5	5	430	3	120
BR4	Revolver	.44 Rem. Magnum	VM/FK/WK	15,6	5	5	440	3	120
BR5	Gewehr	5,56x45	VM/SP/SCP	4	10	10	950	3	120
BR6	Gewehr	7,62x51	VM/SP/WK	9,5	10	10	830	3	120
BR7	Gewehr	7,62x51	VM/SP/HK	9,8	10	10	820	3	120
SG1	Flinte	12/70	Massivge- schoss	31	10	10	420	1	-
SG2	Flinte	12/70	Massivge- schoss	31	10	10	420	3	125

RK = Rundkopf, VM = Vollmantel, WK = Weichkern, FK = Flachkopf, KS = Kegelspitz, SP = Spitz, SCP = Weichkern mit Stahlpenetrator, HK = Hartkern